

# Multi-Flask Shaker VKS 75 A control



## Description

Big heavy-duty shaker VKS 75 A control with digital display and programmable control has an orbital shaking motion, a speed range of 30 - 200 rpm and a stroke of 26 mm. The VKS 75 A control is ideally suited for high loads up to 75 kg. **(floor installation only!)**

### Basic Equipment

Basic device **without shaking plate, without rack system**  
With digital display and programmable control

### Loading Capacity

Erlenmeyer flasks 500 ml	32 pieces
Erlenmeyer flasks 2000 ml	12 pieces
Separating funnels 1000 ml	6 pieces

You will find further loading possibilities [here](#)

[Loading details](#) against shaking speed

### Option:

[Control interface](#)

[USB interface](#)

## Details

<b>Motion:</b>	orbital
<b>Shaking platform:</b>	760 x 600 mm
<b>Max. load:</b>	75 kg
<b>Shaking Speed:</b>	30 - 200 rpm, in steps of 5
<b>Stroke:</b>	26 mm
<b>Runtime:</b>	programmable / continuous
<b>Order no.:</b>	6111 000
<b>Accessory:</b>	Shaking plate VKS (1-storey) Rack System Combifix VKS A Rack System Combifix VKS B Rack System Combifix VKS C Universal tray VKS 1-storey Rack System VKS (2-storey) Rack System VKS "Giant" (3-storey)

## Technical specifications

<b>Electrical supply:</b>	100 - 240 V, 50 / 60 Hz please indicate in case of order
<b>Enclosure protection:</b>	IP 21
<b>Heat emission:</b>	max. 45 W
<b>Ambient temperature:</b>	5°C to 50°C
<b>Relative humidity:</b>	~ 85 %
<b>Dimensions (w x d x h):</b>	1050 x 835 x 250 mm
<b>Weight:</b>	110 kg